

TITLE OF THE INVENTION

ELECTRONIC CAMERA

CROSS-REFERENCE TO RELATED APPLICATION

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 11-029820, filed February 8, 1999;
the entire contents of which are incorporated herein
by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates to an electronic
camera to obtain electric image data by imaging a
subject image, and especially, to an electronic camera
which comprises a print mechanism.

15 Recently, an electronic camera (digital still
camera) to image the subject image by the CCD imaging
element etc., and to memorize the obtained image data
to record mediums such as compact flash (CF) and Smart
Media (SSFDC) has been put to practical use. It is
20 expected that this electronic camera will spread more
and more in the future because of the small size,
lightness, and in addition, the rewritable of image
data.

By the way, in the typical optical camera, a
camera which prints taking picture image at the same
25 time as taking picture (instant photograph by diffusion
transfer method, and Polaroid method, etc.), so-called
instant camera, has been put to practical use. In an

000020-11200500

electronic camera, a camera which enables the printout immediately after taking a picture is variously proposed by providing the print mechanism to the camera in itself.

5 However, an electronic camera which comprises a print mechanism has the following disadvantages. A comparatively large current is required and it also takes time for the print operation. On the other hand, in general, since a small battery is used for the power
10 supply, the power supply capacity is small. Therefore, the power supply remainder becomes insufficient in the print processing, an irregular print is occurred, and the print processing ends on the way occasionally. Here, when the print processing is interrupted when
15 the print mechanism is accompanied by the chemical treatment such as the diffusion transfer method, the one piece becomes useless.

 In an electronic equipment, the technique which urges the exchange of the battery has been adopted by
20 checking the battery remainder (reduced-voltage check) and putting out warning when the remainder of the battery becomes below a predetermined constant value. However, in an electronic camera, the load is different in each of operations such as taking a picture, the
25 record, the reproduction, and the print. Optimal power supply management cannot be performed by uniformly performing the reduced-voltage check for these

0050041-000000

operations.

For example, when the check level is determined according to the record, the case where the print which requires a large current more than the record cannot
5 be performed is occurred. Oppositely, when the check level is determined according to the print, the user will exchange the battery by the reduced-voltage check even if there is a sufficient battery remainder for taking a picture and the record, though it is
10 insufficient to the print.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide an electronic camera which can use a built-in battery to its maximum without uselessness, and can prevent
15 failing of the print, with the configuration which comprises the print mechanism to print out the taking a picture image.

To solve the above-mentioned subject matter, the present invention adopts the following configurations.

20 An electronic camera of present invention is characterized by comprising: an electronic imaging section which performs a photoelectron conversion of a subject image to generate an electric image information; a print section to print an image obtained from
25 the image information by the electronic imaging section on a printing paper; a record section to record the image information by the electronic imaging section on

a record medium; a mode select section to select one camera mode from among a plurality of camera modes; a power supply remainder detection section to detect a remainder to be able to supply the power supply; 5 and a power supply remainder judgment section to set a level necessary for executing an operation corresponding to a camera mode selected by the mode select section according to each of the plurality of modes and to judge whether a detected remainder is equal to or 10 larger than a setting level.

Another electronic camera of present invention, which is driven by a battery, is characterized by comprising: an imaging section which converts a subject image into image data; a record section which records 15 the image data on a detachable record medium; a print section which prints the image data in a predetermined print form; a battery remainder evaluation section which compares a remainder of the battery loaded into the electronic camera with a predetermined judgment 20 level; and a sequence controller which controls a camera sequence based on the comparison result, wherein the sequence controller applies a different judgment level to the battery remainder evaluation section at start of an operation of the print section and in a 25 print operation. In this case, the sequence controller includes a direct print mode which transfers directly to the print section without transferring the image

data to the record section.

According to an electronic camera of the present invention, since the level corresponding to the camera mode is set, and it is judged whether the detected
5 power supply remainder is more than the setting level, optimal power supply management corresponding to the mode can be performed.

Here, preferable manners of the present invention are as follows.

10 (1) The power supply remainder judgment section sets a setting level at a print mode lower than a level at a record mode to record an image which is taken by the electronic imaging section in the record medium.

(2) The power supply remainder judgment section
15 set a setting level of the print start at the print mode higher than a setting level of modes (for example, record mode which records the image taken by the electronic imaging section on the record medium) other than the print mode.

20 (3) The power supply remainder judgment section sets a setting level at starting a print at a print mode is set higher than a setting level at a record mode to record an image which is taken by the electronic imaging section in the record medium, and
25 sets a setting level at the print mode is set lower than a setting level at the record mode to record the image which is taken by the electronic imaging section

in the record medium.

In the above-mentioned each electronic camera, by setting the reduced-voltage check level high before starting the print, the inconvenience such as becoming of the power supply remainder insufficient during printing can be avoided, and the print processing can surely be performed to the last minute. The print can be prevented from being interrupted by setting the reduced-voltage check level low during printing even if the power supply remainder decreases during printing. These are especially valid for the print method like the diffusion transfer method such that the print fails and a photosensitive form becomes useless when the print processing is interrupted.

(4) The power supply remainder judgment section sets a level corresponding to a mode at starting a taking a picture to a level until the print operation of the image is normally completed, at a direct print mode which performs only a print operation without recording an image taken by the electronic imaging section on the record medium. In the direct print mode, at the start of the taking a picture, the print completion can be guaranteed as long as taking a picture is permitted by setting the level corresponding to the mode at the level until the print of the image is normally completed.

(5) In the above-mentioned each of electronic

cameras, the print section has a luminescence section to expose a photosensitive form based on the image information obtained by the electronic imaging section and a transportation section to transport a photo-sensitive form.

Even if the battery remainder is insufficient to the print processing, it is usual to be able to use for other processings. In the present invention, by switching the setting level according to the camera mode, it can be judged that the battery with a little remainder can be used in case of which mode, as a result, the battery can be used without uselessness to the last minute. For example, even if a remainder becomes a capacity which cannot be used to the print, when it is possible to use sufficiently to imaging and the record, by prohibiting printing, but permitting only imaging and the record, etc., it becomes possible to use the battery to the last minute.

According to the present invention, in the configuration which comprises the print mechanism to print out the image after taking a picture, since the reduced-voltage check level is changed according to various operation modes to check the power supply, optimal power supply management can be performed anytime. Especially, by raising the reduced-voltage check level before starting the print and setting the reduced-voltage check level low during printing, the

print can surely be prevented from being interrupted according to the power supply remainder.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is block diagram which shows basic configuration of electronic camera which comprises print mechanism;

FIG. 2 is block diagram which shows specific configuration of print mechanism;

procedure in the third embodiment at taking a picture mode; and

FIG. 6 is a flow chart which shows processing procedure in the fourth embodiment at print mode.

5 DETAILED DESCRIPTION OF THE INVENTION

Hereafter, details of the present invention will be explained with the embodiment referring to the drawings.

(First Embodiment)

10 FIG. 1 is a block diagram which shows configuration of electronic camera having print function according to the first embodiment of the present invention.

An electronic camera according to the first
15 embodiment has imaging section 10, image data processing section 20, image data record and display section 30, control section 40, operation section 50, power supply section 60, and print section 70, in roughly classified.

20 Imaging section 10 has imaging lens 11, CCD imaging element 12, imaging circuit 13, A/D converter 14, correction circuit 15 which performs white balance, and the gamma correction, etc., and frame memory 16, etc. Imaging section 10 images the subject image taken
25 through the optical system, which includes imaging lens 11, on CCD imaging element 12, and converts the imaged image data into a digital signal with A/D converter 14.

Imaging section 10 performs the white balance and the gamma correction, etc. with correction circuit 15, and thereafter stores images in frame memory 16 one by one.

Image data processing section 20 has CPU 2 which
5 comprises image compression function section 21, image expansion function section 22, frame memory control function section 23, record medium access function section 24, and print data manufacturing function section 25. Image data processing section 20 has the
10 following functions. Image data processing section 20 stores the plurality of image data stored in said frame memory 16 to the record buffer not shown in the figure by compressing the image one by one, expands the image data stored in this record buffer, and sends to FIFO
15 memory 34 of image data record and display section 30. In addition, image data processing section 20 accesses record medium 33 of image data record and display section 30.

Image data record and display section 30 has
20 backlight 31, record medium I/F 32, record medium 33 such as the flash memory card, display FIFO memory 34, video encode circuit 35, TFT driver circuit 36, TFT liquid crystal panel 37, video output circuit 38, and video output terminal 39. Image data record and
25 display section 30 has the following functions. Image data record and display section 30 reads the image data recorded in the record buffer and records in record

medium 33. Image data record and display section 30 reads the image data recorded in record medium 33, sends to the display system, and displays the image.

5 The image data sent to the display system is temporarily stored in display FIFO memory 34. The image data read from display FIFO memory 34 is converted into a video signal with video encode circuit 35 and the character etc. are added thereto. Then, on one hand, a video signal to which this character etc. are added is supplied to TFT liquid crystal panel 37 through TFT driver circuit 36, and displayed as a subject image. On the other hand, it is output from a video output terminal 39 to the outside as an image signal through video output circuit 38.

10 15 Control section 40 is mainly constructed by CPU 1 which comprises system control function section 41, print mechanism control function section 42, and various other function sections (for example, compression rate change function section and pixel number change function section, etc.). Control section 20 40 totally controls the entire systems of imaging section 10, image data processing section 20, and image data record and display section 30, etc.

25 Actuator driver circuit 44 to drive actuator 43 which includes zooming motor or AF motor, etc., flash control circuit 46 to control luminescence of flash 45, external data I/F 47 to exchange data with personal

limited to the voltage, but may be a multiplication
the amount of the current.

As described above, optimal power supply
management can be performed in this embodiment anytime
5 by changing the reduced-voltage check level according
to the camera mode. Therefore, since taking a picture
and the print are prohibited, and the record and the
reproduction, etc. are permitted, when it is an
sufficient battery remainder for the record and the
10 reproduction, even if the battery has a remainder which
can not use for, for example, the print processing, the
battery can be used to the last minute.

(Second Embodiment)

Since a basic configuration of an electronic
15 camera in this embodiment is similar to FIG. 1,
therefore drawings will be omitted.

In this embodiment, when the print start is
directed by the user as shown in the flow chart of
FIG. 4, first, the reduced-voltage check level is set
20 in level A' (step S41). Here, level A' is assumed to
be lower level than usual setting value D (level A' <
level D). Usual setting value D is a setting level
which is suitable for, for example, the record mode.
Subsequently, the print operation is performed
25 (step S42). Then, when the print operation ends,
the reduced-voltage check level is returned to level D
(step S43).

For the instant camera method in which the print mechanism uses the diffusion transfer method, if the print processing stops on the way, one piece becomes quite useless. Therefore, an interruption of the print should be avoided, first. Then, in this embodiment, by setting level A' which is the reduced-voltage check level in the print mode low, completion of the print is set to be top priority. Therefore, even if the battery remainder a little, the print can be prevented from interrupting.

As described above, in this embodiment, the print can be prevented from interrupting by setting the reduced-voltage check level in the print mode in a low value. Therefore, this embodiment is especially valid when the print mechanism which uses the diffusion transfer method is used.

(Third Embodiment)

Since a basic configuration of an electronic camera in this embodiment is similar to FIG. 1, therefore drawings will be omitted.

In this embodiment, as shown in the flow chart of FIG. 5, when the print start is directed by the user, the power supply remainder is checked first by reduced-voltage check level A" (step S51). Then, it is judged whether the reduced-voltage check is OK (step S52). Here, level A" which is the reduced-voltage check level is higher level than level D which is a usual level.

same time as taking a picture, as shown in the flow chart of FIG. 6.

First, when the print start is directed by the user, it is judged whether it is a direct print (step S61). When it is judged that it is a direct print, the power supply is checked in the reduced-voltage check level P considered from taking a picture to the print operation (step S62), and when it is judged that it is not a direct print, the battery remainder is checked at level C ($C < P$) which is a suitable reduced-voltage check level for the taking a picture mode or level D which is a usual reduced-voltage check level (step S63).

Next, it is judged whether the reduced-voltage
15 check is OK (step S64). When it is judged that the
reduced-voltage check is OK, the taking a picture
operation is performed (step S65). Then, it is judged
whether it is a direct print again (step S66). When it
is a direct print, the print operation is performed
20 (step S67), and when it is not a direct print, the
record on the record medium is performed (step S68).

One side, when it is judged that the reduced-voltage check is not OK in step S64, the reduced-voltage warning is displayed without performing the taking a picture operation (S69).

As described above, in this embodiment, when the user directs a direct print, it is possible to print

directly when there is the sufficient battery remainder
by checking the reduced-voltage at high level P, which
is necessary for direct print. However, when the
battery remainder is insufficient, the reduced-voltage
warning is displayed, and a direct print is prohibited.
Therefore, the inconvenience such that direct print
performs even though the battery remainder is
insufficient, the print is interrupted during printing
after taking a picture, and the form becomes useless,
can be prevented beforehand.

The present invention is not limited to each
embodiment mentioned above. The configuration of the
print mechanism is not limited to a so-called instant
camera method to obtain the positive image directly by
using the diffusion transfer method, and the printer of
the thermal transfer type, the ink-jet type, and the
sublimation type may be used.

The configuration of the main body of the camera
is not limited to a camera as shown in FIG. 1, and may
be a camera which images subject image by the imaging
element such as CCD to generate an electric image
information, and memorize this image information to the
flash memory, etc. In the method of batch display and
print out the image to printing paper at the same time
as taking a picture, it is also possible to omit the
memory such as the flash memory.

The present invention can be carried out by

transforming within the range of scope of the invention.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the present invention in its broader aspects is not limited to the specific details, representative devices, and illustrated examples shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.